





4/3-Way valves - manually actuated 1/8" and 1/4" Series HDV



Design type	Rotary slide valve, manually actuated
Connection	G1/8" and G1/4" according to ISO228/1
Pressure range	0 up to 12 bar
Materials	Body Anodized aluminium, Slide valve Polyamide, Seals NBR
Mounting type	Through holes in the valve body
Mounting position	any
Medium	lubricated compressed air
Medium temperature	-10°C up to +60°C
Ambient temperature	-20°C up to +55°C

Dimensions

		 Center position closed  Center position open
---	--	--

Connection A	Nominal size	C	D	E	F	G	H	I	K	L	M	N	Function Center position	Flow rate [Nl/min]	Weight [kg]	Type
G1/8" lateral	5	56	46	17	-	-	35	35	-	4,5	105	70	closed	480	0,253	HDV-4001-N
G1/4" lateral	7	67	55	21	-	-	43	43	-	5,5	110	80	closed	1050	0,352	HDV-4002-N
G1/8" bottom	5	56	46	17	6	40	35	35	11	4,5	105	70	closed	480	0,230	HDV-4001-I
G1/8" lateral	5	56	46	17	-	-	35	35	-	4,5	105	70	open	480	0,253	HDV-4101-N
G1/4" lateral	7	67	55	21	-	-	43	43	-	5,5	110	80	open	1050	0,352	HDV-4102-N
G1/8" bottom	5	56	46	17	6	40	35	35	11	4,5	105	70	open	480	0,230	HDV-4101-I

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Way-valves - mechanically / manually, logic units / Rotary valves

