



## Silencer Series SLS



|                      |                                                                                                                                                               |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Design type          | Silencer with silencer element made of stainless steel wire                                                                                                   |
| Threaded connections | M5 after ISO R/262, G1/8" up to G1/2" after ISO228/1                                                                                                          |
| Material             | M5: Brass connection thread, Damper component Stainless steel wire<br>1/8"...1/2": Connection thread brass nickel-plated, Damper element stainless steel wire |
| Function             | for noise attenuation and against dirt ingress into devices                                                                                                   |
| Mounting position    | any                                                                                                                                                           |
| Medium               | Compressed air, neutral gases                                                                                                                                 |
| Medium temperature   | -10°C...+70°C                                                                                                                                                 |
| Operating pressure   | max. 12bar                                                                                                                                                    |
| Note                 | If contaminated, the blow-off capacity decreases. The silencers can be cleaned with cleaning benzine or solvent.                                              |

### Dimensions



| D1    | L1 | L2 | CH | Weight [g] | Type       |
|-------|----|----|----|------------|------------|
| M5    | 4  | 9  | 8  | 5          | SLS-MM5-BS |
| G1/8" | 6  | 15 | 13 | 6          | SLS-M18-NS |
| G1/4" | 7  | 18 | 16 | 10         | SLS-M14-NS |
| G3/8" | 8  | 20 | 19 | 16         | SLS-M38-NS |
| G1/2" | 10 | 22 | 24 | 25         | SLS-M12-NS |

Illustrations non-binding  
Design, dimensional and material changes reserved

Pneumatics / Flow control valves / Silencer / Silencer Series SLS-NS

