


Spojnice obostrano zaporno DN 5mm Serija C0.S50-B




Konstrukcija	Utičnice spojnice i utikači spojnice, obostrano zaporno
Nazivni prečnik	DN 5mm
Materijali	Telo, ventil i konektor Mesing, Opruga i kuglica Nerđajući čelik, Zaptivka NBR
Nominalni protok	180NI/min pri 6 bar (Δp 0,5bar)
Medij	Komprimovani vazduh, neutralni gasovi i Tečnosti
Temperatura medijuma	-20°C...+100°C
Radni pritisak	-0,87...35bar


C0CS50-M Utičnica spojnice - Spoljašnji navoj

	A	D	L	L1	SW	Težina [g]	Tip
	G1/8"	16	36	7	14	28	C0CS50-M18-B
	G1/4"	16	38	9	17	36	C0CS50-M14-B

C0CS50-F Utičnica spojnice - Unutrašnji navoj


	A	D	L	L1	SW	Težina [g]	Tip
	G1/8"	16	36	9	14	30	C0CS50-F18-B
	G1/4"	16	38	9	17	39	C0CS50-F14-B

C0CS50-H Utičnica spojnice - Nastavak za crevo


	Unutrašnji prečnik creva	D	L	L1	CH	Težina [g]	Tip
	4	16	46	17	14	25	C0CS50-H04-B
	6	16	46	17	14	27	C0CS50-H06-B
	9	16	46	17	14	27	C0CS50-H09-B




C0PS50-M Priključni utikač - Spoljašnji navoj

	A	L	L1	CH	Težina [g]	Tip
	G1/8"	40	7	14	95	C0PS50-M18-B
	G1/4"	42	9	17	95	C0PS50-M14-B

C0PS50-H Priključni utikač - Nastavak za crevo

	Unutrašnji prečnik creva	L	L1	CH	Težina [g]	Tip
	4	50	17	14	22	C0PS50-H04-B
	6	50	17	14	23	C0PS50-H06-B
	9	50	17	14	23	C0PS50-H09-B

C0PS50-F Priključni utikač - Unutrašnji navoj

	A	L	L1	CH	Težina [g]	Tip
	G1/8"	40	7	14	93	C0PS50-F18-B
	G1/4"	42	7	17	93	C0PS50-F14-B

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica DN 5 - mesing - dvosmerno zaptivanje

