


Spojke DN 7,2mm Serija C0.72-H




Konstrukcija	Vtičnice sklopov in vtiči sklopov, enostransko zaporno
Nazivni premer	DN 7,2mm
Materiali	Ohišje, ventil in konektor Nerjavno jeklo 1.4305, Vzmet nerjavno jeklo 1.4310, Tesnilo FKM
Nazivni pretok	maks.1200Nl/min pri 6 bar (Δp 0,5bar)
Medij	Stisnjen zrak, nevtralni plini in tekočine
Temperatura medija	-20°C...+200°C
Obratovalni tlak	-0,80...35bar


C0C72-M Vtičnica sklopke - zunanji navoj

	D1	D2	L1	L2	CH	Teža [g]	Tip
	G1/4"	27	9	41	22	82	C0C72-M14-H
	G3/8"	27	10	42	22	82	C0C72-M38-H
	G1/2"	27	12	44	24	95	C0C72-M12-H

C0C72-F Vtičnica sklopke - notranji navoj

	D1	D2	L1	L2	CH	Teža [g]	Tip
	G1/4"	27	10,5	41,5	22	83	C0C72-F14-H
	G3/8"	27	10,5	41,5	22	83	C0C72-F38-H
	G1/2"	27	12	43	24	92	C0C72-F12-H

C0C72-H Vtičnica sklopke - Cevni nastavek

	notranji premer cevi	D1	D2	L2	CH	Teža [g]	Tip
	6	7,5	27	56	22	92	C0C72-H06-H
	9	10,5	27	56	22	92	C0C72-H09-H
	13	14,5	27	56	22	95	C0C72-H13-H




C0P72-M vtični spojnik - zunanji navoj

	D1	L1	CH	Teža [g]	Tip
	G1/4"	33,5	17	20	C0P72-M14-H
	G3/8"	33,5	19	24	C0P72-M38-H
	G1/2"	36	24	39	C0P72-M12-H

C0P72-F vtični spojnik - notranji navoj

	D1	L1	CH	Teža [g]	Tip
	G1/4"	33	17	24	C0P72-F14-H
	G3/8"	33	19	24	C0P72-F38-H
	G1/2"	35	24	39	C0P72-F12-H

C0P72-H vtični spojnik - Cevni nastavek

	notranji premer cevi	D1	L1	Teža [g]	Tip
	6	7,5	44	17	C0P72-H06-H
	9	10,5	44	18	C0P72-H09-H
	13	14,5	44	25	C0P72-H13-H

Ilustracije nezavezujoče

Pridržujemo si pravico do konstrukcijskih, dimenzijskih in materialnih sprememb

Pnevmatika / Vezni elementi in spojke / Spojke / Vtična spojka standard / Spojke DN 7,2 - legirano jeklo 1.4305

