


Couplings DN 7,2mm Series C0.72-H




Design type	Coupling sockets and coupling plugs, single shut-off
Nominal size	DN 7,2mm
Materials	Body, valve and connector Stainless steel 1.4305, Stainless steel spring 1.4310, Seal FKM
Nominal flow rate	max.1200NI/min at 6 bar (Δp 0,5bar)
Medium	Compressed air, neutral gases and liquids
Medium temperature	-20°C...+200°C
Operating pressure	-0,80...35bar


C0C72-M Coupling socket - Male thread

	D1	D2	L1	L2	CH	Weight [g]	Type
	G1/4"	27	9	41	22	82	C0C72-M14-H
	G3/8"	27	10	42	22	82	C0C72-M38-H
	G1/2"	27	12	44	24	95	C0C72-M12-H

C0C72-F Coupling socket - Female thread

	D1	D2	L1	L2	CH	Weight [g]	Type
	G1/4"	27	10,5	41,5	22	83	C0C72-F14-H
	G3/8"	27	10,5	41,5	22	83	C0C72-F38-H
	G1/2"	27	12	43	24	92	C0C72-F12-H

C0C72-H Coupling socket - Hose nozzle

	Hose inner diameter	D1	D2	L2	CH	Weight [g]	Type
	6	7,5	27	56	22	92	C0C72-H06-H
	9	10,5	27	56	22	92	C0C72-H09-H
	13	14,5	27	56	22	95	C0C72-H13-H




C0P72-M Coupling plug - Male thread

	D1	L1	CH	Weight [g]	Type
	G1/4"	33,5	17	20	C0P72-M14-H
	G3/8"	33,5	19	24	C0P72-M38-H
	G1/2"	36	24	39	C0P72-M12-H

C0P72-F Coupling plug - Female thread

	D1	L1	CH	Weight [g]	Type
	G1/4"	33	17	24	C0P72-F14-H
	G3/8"	33	19	24	C0P72-F38-H
	G1/2"	35	24	39	C0P72-F12-H

C0P72-H Coupling plug - Hose nozzle

	Hose inner diameter	D1	L1	Weight [g]	Type
	6	7,5	44	17	C0P72-H06-H
	9	10,5	44	18	C0P72-H09-H
	13	14,5	44	25	C0P72-H13-H

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Couplings / Coupling plug Standard / Couplings DN 7,2 - Stainless steel 1.4305

