


Filter 3/4" Series F




Design type	Filter with plastic filter element and protective cage
Connection	G3/4" according to ISO228/1
Materials	Housing Acetal resin (POM), Threaded connections Brass, Condensate reservoir Polyamide, Protective cage PE, Seals NBR
Function	Compressed air filtration
Mounting type	Installation in piping system or Wall mounting
Mounting position	vertical, Condensate container downward
Medium	Compressed air
Medium temperature	+5...+50°C
Ambient temperature	+5...+50°C
Inlet pressure	max. 12,5bar, 1,5-10bar with automatic drain valve K-SA
Filter elements	see "Order code"
Flow direction	is marked by an arrow
Condensate drain valve	manual or semi-automatic
Volume Condensate container	140cm ³

Order code

		F - 34 - 20 - PE - SS					
Connection	3/4"	34					
Filter element	20µm	20					
	5µm	5					
Reservoir	Plastic bowl with protective guard	PE					
Drain valve	Manual drain valve					SS	
	automatic drain valve					SA	




Dimensions



Connection G	A	B	C	D	E	F	H	I	J	Weight [approx. kg]	Type
G3/4"	31	172	138	40	5	5,5	17,5	204	63	0,67	F-34-...-PE-S.

Flow diagram, Filter element 20µm



The diagram shows various inlet pressures up to a maximum pressure drop of 1 bar

Illustrations non-binding
Design, dimensional and material changes reserved