


Pressure gauge fitting Series C-MAVE



Design type	Compression fitting with cutting ring, with sealing cone and O-ring
Tube outside diameter	6...12mm
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Seal	NBR (FKM on request)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-35...100°C
Operating pressure	Nominal pressure according to table

Dimensions



Series	PN [bar]	Tube diameter	G	m	L1	L2	L3	CH1	CH2	Type
L	315	6	1/4	12x1,5	4,5	14,5	21,5	19	14	C-MAVE06LR1/4
		8	1/4	14x1,5	4,5	14,5	21,5	19	17	C-MAVE08LR1/4
		10	1/4	16x1,5	4,5	14,5	22	19	19	C-MAVE10LR1/4
		12	1/4	18x1,5	4,5	14,5	22	19	22	C-MAVE12LR1/4
S	630	6	1/2	14x1,5	5	20	23	30	17	C-MAVE06LR1/2
		8	1/2	16x1,5	5	20	23,5	30	19	C-MAVE08LR1/2
		10	1/2	18x1,5	5	20	24,5	30	22	C-MAVE10LR1/2
		12	1/2	20x1,5	5	20	24,5	30	24	C-MAVE12LR1/2

Illustrations non-binding
Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Adjustable manometer fitting Series C-MAVE

