



Straight male stud fitting Series C-EGE-UNF



Design type	Compression fitting with cutting ring, with sealing cone and O-ring
Tube outside diameter	6...42mm
Material	Steel galvanized
(according to standard)	EN ISO 8434-1 (DIN 2353)
Seal	NBR (FKM on request)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-35...+100°C
Operating pressure	Nominal pressure according to table



Dimensions



Series	PN [bar]	Tube diameter	m	W	D1	L1	L2	CH1	CH2	Type
L	315	6	12x1,5	7/16-20	13,8	24,4	9,1	14	14	C-EGE06L7/16UNF
		8	14x1,5	7/16-20	13,8	24,4	9,1	14	17	C-EGE08L7/16UNF
		10	16x1,5	9/16-18	18,8	27,5	10	19	19	C-EGE10L9/16UNF
		12	18x1,5	3/4-16	21,8	33,9	11,1	22	22	C-EGE12L3/4UNF
		15	22x1,5	7/8-14	26,8	32,3	12,7	27	27	C-EGE15L7/8UNF
		18	26x1,5	7/8-14	26,8	31,8	12,7	27	32	C-EGE18L7/8UNF
	160	22	30x2	11/16-12	31,8	32,4	15,1	32	36	C-EGE22L11/16UNF
		28	36x2	15/16-12	40,8	34,9	15,1	41	41	C-EGE28L15/16UNF
		35	45x2	15/8-12	49,8	42,4	15,1	50	50	C-EGE35L15/8UNF
		42	52x2	17/8-12	54,8	46,4	15,1	55	60	C-EGE42L17/8UNF
S	630	6	14x1,5	7/16-20	13,8	26,9	9,1	14	17	C-EGE06L7/16UNF
		8	16x1,5	9/16-18	18,8	29,5	10	17	19	C-EGE08L9/16UNF
		10	18x1,5	9/16-18	18,8	30,5	10	17	22	C-EGE10L9/16UNF
		12	20x1,5	3/4-16	21,8	34,4	11,1	22	24	C-EGE12L3/4UNF
		14	22x1,5	7/8-14	26,8	36,3	12,7	27	27	C-EGE14L7/8UNF
	400	16	24x1,5	7/8-14	26,8	36,8	12,7	27	30	C-EGE16L7/8UNF
		20	30x2	11/16-12	31,8	42,9	15,1	32	36	C-EGE20L11/16UNF
		25	36x2	15/16-12	40,8	47,9	15,1	41	46	C-EGE25L15/16UNF
		30	42x2	15/8-12	49,8	50,9	15,1	50	50	C-EGE30L15/8UNF
	315	38	52x2	17/8-12	54,8	59,9	15,1	55	60	C-EGE38L17/8UNF

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Adjustable male stud adapter Series C-EGE-UNF

Version 10

138484 / Generated 2026/40 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

