

Male elbow screw-in fitting Series C-WE-R-K



Main body with nut and cutting ring




B4-Cutting ring




B3-Cutting ring

Design type	Compression fitting with cutting ring, with B3 or B4 cutting ring
Male thread	1/8...1 1/2" BSPT, with elastic seal
Tube outside diameter	4...42mm
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	B3-Cutting ring -40...+120°C B4-Cutting ring NBR -25...+100°C (FKM on request)
Operating pressure	Nominal pressure according to table


Dimensions



Main body



with B4 cutting ring






with B3 cutting ring

Series	PN [bar]	Tube diameter	G	L1	L2	L3	L4	L5	CH1	CH2	Type Main body	Type B4 ring	Type B3 ring
LL	100	4	1/8	15	11	17	8	21	9	10	C-WE04LLR1/8KX	-	C-WE04LLR1/8K
		6	1/8	15	9,5	17	8	21	9	12	C-WE06LLR1/8KX	-	C-WE06LLR1/8K
		8	1/8	17	11,5	20	8	23	12	14	C-WE08LLR1/8KX	-	C-WE08LLR1/8K
L	315	6	1/8	19	12	20	8	27	12	14	C-WE06LR1/8KX	C-WE06ZLR1/8K	C-WE06LR1/8K
		8	1/4	21	14	26	12	29	12	17	C-WE08LR1/4KX	C-WE08ZLR1/4K	C-WE08LR1/4K
		10	1/4	22	15	27	12	30	14	19	C-WE10LR1/4KX	C-WE10ZLR1/4K	C-WE10LR1/4K
		12	3/8	24	17	28	12	32	17	22	C-WE12LR3/8KX	C-WE12ZLR3/8K	C-WE12LR3/8K
		15	1/2	28	21	34	14	36	19	27	C-WE15LR1/2KX	C-WE15ZLR1/2K	C-WE15LR1/2K
		18	1/2	31	23,5	36	14	40	24	32	C-WE18LR1/2KX	C-WE18ZLR1/2K	C-WE18LR1/2K
	160	22	3/4	35	27,5	42	16	44	27	36	C-WE22LR3/4KX	C-WE22ZLR3/4K	C-WE22LR3/4K
		28	1	38	30,5	48	18	47	36	41	C-WE28LR1KX	C-WE28ZLR1K	C-WE28LR1K
		35	1 1/4	45	34,5	54	20	56	41	50	C-WE35LR11/4KX	C-WE35ZLR11/4K	C-WE35LR11/4K
		42	1 1/2	51	40	61	22	63	50	60	C-WE42LR11/2KX	C-WE42ZLR11/2K	C-WE42LR11/2K



Dimensions

													
Main body				with B4 cutting ring						with B3 cutting ring			
Series	PN [bar]	Tube diameter	G	L1	L2	L3	L4	L5	CH1	CH2	Type Main body	Type B4 ring	Type B3 ring
S	630	6	1/4	23	16	26	12	31	12	17	C-WE06SR1/4KX	C-WE06ZSR1/4K	C-WE06SR1/4K
		8	1/4	24	17	27	12	32	14	19	C-WE08SR1/4KX	C-WE08ZSR1/4K	C-WE08SR1/4K
		10	3/8	25	17,5	28	12	34	17	22	C-WE10SR3/8KX	C-WE10ZSR3/8K	C-WE10SR3/8K
		12	3/8	29	21,5	28	12	38	17	24	C-WE12SR3/8KX	C-WE12ZSR3/8K	C-WE12SR3/8K
		14	1/2	30	22	32	14	40	19	27	C-WE14SR1/2KX	C-WE14ZSR1/2K	C-WE14SR1/2K
	400	16	1/2	33	24,5	32	14	43	24	30	C-WE16SR1/2KX	C-WE16ZSR1/2K	C-WE16SR1/2K
		20	3/4	37	26,5	42	16	48	27	36	C-WE20SR3/4KX	C-WE20ZSR3/4K	C-WE20SR3/4K
		25	1	42	30	48	18	54	36	46	C-WE25SR1KX	C-WE25ZSR1K	C-WE25SR1K
		30	1 1/4	49	35,5	54	20	62	41	50	C-WE30SR11/4KX	C-WE30ZSR11/4K	C-WE30SR11/4K
315	38	1 1/2	57	41	61	22	72	50	60	C-WE38SR11/2KX	C-WE38ZSR11/2K	C-WE38SR11/2K	
L	315	6	1/4	21	14	26	12	29	12	14	C-WE06LR1/4KX	C-WE06ZLR1/4K	C-WE06LR1/4K
		8	1/8	21	14	22	8	29	12	17	C-WE08LR1/8KX	C-WE08ZLR1/8K	C-WE08LR1/8K
		8	3/8	23	16	28	12	31	17	17	C-WE08LR3/8KX	C-WE08ZLR3/8K	C-WE08LR3/8K
		8	1/2	26	19	34	14	34	19	17	C-WE08LR1/2KX	C-WE08ZLR1/2K	C-WE08LR1/2K
		10	1/8	22	15	22	8	30	14	19	C-WE10LR1/8KX	C-WE10ZLR1/8K	C-WE10LR1/8K
		10	3/8	24	17	28	12	32	17	19	C-WE10LR3/8KX	C-WE10ZLR3/8K	C-WE10LR3/8K
		10	1/2	27	20	34	14	35	19	19	C-WE10LR1/2KX	C-WE10ZLR1/2K	C-WE10LR1/2K
		12	1/4	24	17	28	12	32	17	22	C-WE12LR1/4KX	C-WE12ZLR1/4K	C-WE12LR1/4K
		12	1/2	27	20	34	14	34	19	22	C-WE12LR1/2KX	C-WE12ZLR1/2K	C-WE12LR1/2K
		15	3/8	28	21	30	12	36	19	27	C-WE15LR3/8KX	C-WE15ZLR3/8K	C-WE15LR3/8K
		18	3/4	34	26,5	42	16	43	27	32	C-WE18SR3/4KX	C-WE18ZLR3/4K	C-WE18LR3/4K
		S	630	12	1/2	28	20,5	32	14	37	19	24	C-WE12SR1/2KX
14	3/8			30	22	30	12	40	19	27	C-WE14SR3/8KX	C-WE14ZSR3/8K	C-WE14SR3/8K
16	3/8			33	24,5	37	12	43	24	30	C-WE16SR3/8KX	C-WE16ZSR3/8K	C-WE16SR3/8K
20	1/2			37	26,5	36	14	48	27	36	C-WE20SR1/2KX	C-WE20ZSR1/2K	C-WE20SR1/2K
400	25		3/4	42	30	42	16	54	36	46	C-WE25SR3/4KX	C-WE25ZSR3/4K	C-WE25SR3/4K
	30		1	49	35,5	48	18	62	41	50	C-WE30SR1KX	C-WE30ZSR1K	C-WE30SR1K

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Male elbow Series C-WE-R-K

Version 11

138486 / Generated 2026/40 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

