

Ugaoni uvrtni priključak Serija C-WE-R-K



Osnovno telo sa maticom i sečnim prstenom




B4-Rezni prsten




B3-Rezni prsten

Konstrukcija	Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje
Navoj za uvrtnje	1/8...1 1/2" BSPT, sa elastičnom zaptivkom
Spoljašnji prečnik cevi	4...42mm
Materijal	Čelik pocinkovano
Odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebene materijale
Temperatura medijuma	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -25...+100°C (FKM na upit)
Radni pritisak	Nazivni pritisak prema tabeli


Dimenzije



Osnovno telo



sa B4-rezni prsten






sa B3-rezni prsten

Seriya	PN [bar]	Prečnik cevi	G	L1	L2	L3	L4	L5	CH1	CH2	Tip Osnovno telo	Tip B4-prsten	Tip B3-prsten
LL	100	4	1/8	15	11	17	8	21	9	10	C-WE04LLR1/8KX	-	C-WE04LLR1/8K
		6	1/8	15	9,5	17	8	21	9	12	C-WE06LLR1/8KX	-	C-WE06LLR1/8K
		8	1/8	17	11,5	20	8	23	12	14	C-WE08LLR1/8KX	-	C-WE08LLR1/8K
L	315	6	1/8	19	12	20	8	27	12	14	C-WE06LR1/8KX	C-WE06ZLR1/8K	C-WE06LR1/8K
		8	1/4	21	14	26	12	29	12	17	C-WE08LR1/4KX	C-WE08ZLR1/4K	C-WE08LR1/4K
		10	1/4	22	15	27	12	30	14	19	C-WE10LR1/4KX	C-WE10ZLR1/4K	C-WE10LR1/4K
		12	3/8	24	17	28	12	32	17	22	C-WE12LR3/8KX	C-WE12ZLR3/8K	C-WE12LR3/8K
		15	1/2	28	21	34	14	36	19	27	C-WE15LR1/2KX	C-WE15ZLR1/2K	C-WE15LR1/2K
		18	1/2	31	23,5	36	14	40	24	32	C-WE18LR1/2KX	C-WE18ZLR1/2K	C-WE18LR1/2K
	160	22	3/4	35	27,5	42	16	44	27	36	C-WE22LR3/4KX	C-WE22ZLR3/4K	C-WE22LR3/4K
		28	1	38	30,5	48	18	47	36	41	C-WE28LR1KX	C-WE28ZLR1K	C-WE28LR1K
		35	1 1/4	45	34,5	54	20	56	41	50	C-WE35LR11/4KX	C-WE35ZLR11/4K	C-WE35LR11/4K
		42	1 1/2	51	40	61	22	63	50	60	C-WE42LR11/2KX	C-WE42ZLR11/2K	C-WE42LR11/2K



Dimenzije

  													
Osnovno telo				sa B4-rezni prsten						sa B3-rezni prsten			
Seriya	PN [bar]	Prečnik cevi	G	L1	L2	L3	L4	L5	CH1	CH2	Tip Osnovno telo	Tip B4-prsten	Tip B3-prsten
S	630	6	1/4	23	16	26	12	31	12	17	C-WE06SR1/4KX	C-WE06ZSR1/4K	C-WE06SR1/4K
		8	1/4	24	17	27	12	32	14	19	C-WE08SR1/4KX	C-WE08ZSR1/4K	C-WE08SR1/4K
		10	3/8	25	17,5	28	12	34	17	22	C-WE10SR3/8KX	C-WE10ZSR3/8K	C-WE10SR3/8K
		12	3/8	29	21,5	28	12	38	17	24	C-WE12SR3/8KX	C-WE12ZSR3/8K	C-WE12SR3/8K
		14	1/2	30	22	32	14	40	19	27	C-WE14SR1/2KX	C-WE14ZSR1/2K	C-WE14SR1/2K
	400	16	1/2	33	24,5	32	14	43	24	30	C-WE16SR1/2KX	C-WE16ZSR1/2K	C-WE16SR1/2K
		20	3/4	37	26,5	42	16	48	27	36	C-WE20SR3/4KX	C-WE20ZSR3/4K	C-WE20SR3/4K
		25	1	42	30	48	18	54	36	46	C-WE25SR1KX	C-WE25ZSR1K	C-WE25SR1K
		30	1 1/4	49	35,5	54	20	62	41	50	C-WE30SR11/4KX	C-WE30ZSR11/4K	C-WE30SR11/4K
315	38	1 1/2	57	41	61	22	72	50	60	C-WE38SR11/2KX	C-WE38ZSR11/2K	C-WE38SR11/2K	
L	315	6	1/4	21	14	26	12	29	12	14	C-WE06LR1/4KX	C-WE06ZLR1/4K	C-WE06LR1/4K
		8	1/8	21	14	22	8	29	12	17	C-WE08LR1/8KX	C-WE08ZLR1/8K	C-WE08LR1/8K
		8	3/8	23	16	28	12	31	17	17	C-WE08LR3/8KX	C-WE08ZLR3/8K	C-WE08LR3/8K
		8	1/2	26	19	34	14	34	19	17	C-WE08LR1/2KX	C-WE08ZLR1/2K	C-WE08LR1/2K
		10	1/8	22	15	22	8	30	14	19	C-WE10LR1/8KX	C-WE10ZLR1/8K	C-WE10LR1/8K
		10	3/8	24	17	28	12	32	17	19	C-WE10LR3/8KX	C-WE10ZLR3/8K	C-WE10LR3/8K
		10	1/2	27	20	34	14	35	19	19	C-WE10LR1/2KX	C-WE10ZLR1/2K	C-WE10LR1/2K
		12	1/4	24	17	28	12	32	17	22	C-WE12LR1/4KX	C-WE12ZLR1/4K	C-WE12LR1/4K
		12	1/2	27	20	34	14	34	19	22	C-WE12LR1/2KX	C-WE12ZLR1/2K	C-WE12LR1/2K
		15	3/8	28	21	30	12	36	19	27	C-WE15LR3/8KX	C-WE15ZLR3/8K	C-WE15LR3/8K
		18	3/4	34	26,5	42	16	43	27	32	C-WE18SR3/4KX	C-WE18ZLR3/4K	C-WE18LR3/4K
		20	1/2	37	26,5	42	16	48	27	36	C-WE20SR1/2KX	C-WE20ZSR1/2K	C-WE20SR1/2K
S	630	12	1/2	28	20,5	32	14	37	19	24	C-WE12SR1/2KX	C-WE12ZSR1/2K	C-WE12SR1/2K
		14	3/8	30	22	30	12	40	19	27	C-WE14SR3/8KX	C-WE14ZSR3/8K	C-WE14SR3/8K
		16	3/8	33	24,5	37	12	43	24	30	C-WE16SR3/8KX	C-WE16ZSR3/8K	C-WE16SR3/8K
	400	20	1/2	37	26,5	42	16	48	27	36	C-WE20SR1/2KX	C-WE20ZSR1/2K	C-WE20SR1/2K
		25	3/4	42	30	48	18	54	36	46	C-WE25SR3/4KX	C-WE25ZSR3/4K	C-WE25SR3/4K
		30	1	49	35,5	54	20	62	41	50	C-WE30SR1KX	C-WE30ZSR1K	C-WE30SR1K

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključici i spojnice za pneumatiku / Priključici sa usečnim prstenom / priključak sa usečnim prstenom - pocinkovani čelik ISO 8434-1 (DIN 2353) / koleno sa spoljnim navojem serije C-WE-R-K

Verzija 10

138486 / Generisano 2026/38 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

