

## Ugaoni uvrtni priključak Serija C-WE-M-71



Osnovno telo sa maticom i sečnim prstenom




B4-Rezni prsten




B3-Rezni prsten

|                         |                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------|
| Konstrukcija            | Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje                                             |
| Navoj za uvrtnje        | M10x1...M48x2, sa elastičnom zaptivkom                                                                      |
| Spoljašnji prečnik cevi | 6...42mm                                                                                                    |
| Materijal               | Nerđajući čelik 1.4571                                                                                      |
| Odgovarajuće standard   | EN ISO 8434-1 (DIN 2353)                                                                                    |
| Medij                   | neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale                                       |
| Temperatura medijuma    | B3-Rezni prsten -60...+200°C<br>B4-Rezni prsten FKM -25...+200°C                                            |
| Radni pritisak          | Nazivni pritisak prema tabeli do 50°C, preko 50°C 4% Redukcija pritiska, preko 100°C 11% Redukcija pritiska |


### Dimenzije



Osnovno telo



sa B4-rezni prsten






sa B3-rezni prsten

| Seriya | PN [bar] | Prečnik cevi | M      | L1 | L2   | L3 | L4 | L5 | CH1 | CH2 | Tip Osnovno telo  | Tip B4-prsten     | Tip B3-prsten    |
|--------|----------|--------------|--------|----|------|----|----|----|-----|-----|-------------------|-------------------|------------------|
| L      | 315      | 6            | 10x1   | 19 | 12   | 20 | 8  | 27 | 12  | 14  | C-WE06LM10X171X   | C-WE06ZLM10X171   | C-WE06LM10X171   |
|        |          | 8            | 12x1,5 | 21 | 14   | 26 | 12 | 29 | 12  | 17  | C-WE08LM12X1,571X | C-WE08ZLM12X1,571 | C-WE08LM12X1,571 |
|        |          | 10           | 14x1,5 | 22 | 15   | 27 | 12 | 30 | 14  | 19  | C-WE10LM14X1,571X | C-WE10ZLM14X1,571 | C-WE10LM14X1,571 |
|        |          | 12           | 16x1,5 | 24 | 17   | 28 | 12 | 32 | 17  | 22  | C-WE12LM16X1,571X | C-WE12ZLM16X1,571 | C-WE12LM16X1,571 |
|        |          | 15           | 18x1,5 | 28 | 21   | 32 | 12 | 36 | 19  | 27  | C-WE15LM18X1,571X | C-WE15ZLM18X1,571 | C-WE15LM18X1,571 |
|        |          | 18           | 22x1,5 | 31 | 23,5 | 36 | 14 | 40 | 24  | 32  | C-WE18LM22X1,571X | C-WE18ZLM22X1,571 | C-WE18LM22X1,571 |
| S      | 630      | 6            | 12x1,5 | 23 | 16   | 26 | 12 | 31 | 12  | 17  | C-WE06SM12X1,571X | C-WE06ZSM12X1,571 | C-WE06SM12X1,571 |
|        |          | 8            | 14x1,5 | 24 | 17   | 27 | 12 | 32 | 14  | 19  | C-WE08SM14X1,571X | C-WE08ZSM14X1,571 | C-WE08SM14X1,571 |
|        |          | 10           | 16x1,5 | 25 | 17,5 | 28 | 12 | 34 | 17  | 22  | C-WE10SM16X1,571X | C-WE10ZSM16X1,571 | C-WE10SM16X1,571 |
|        |          | 12           | 18x1,5 | 29 | 21,5 | 28 | 12 | 38 | 17  | 24  | C-WE12SM18X1,571X | C-WE12ZSM18X1,571 | C-WE12SM18X1,571 |
|        |          | 14           | 20x1,5 | 30 | 22   | 32 | 14 | 40 | 19  | 27  | C-WE14SM20X1,571X | C-WE14ZSM20X1,571 | C-WE14SM20X1,571 |
|        | 400      | 16           | 22x1,5 | 33 | 24,5 | 32 | 14 | 43 | 24  | 30  | C-WE16SM22X1,571X | C-WE16ZSM22X1,571 | C-WE16SM22X1,571 |



## Dimenzije



Osnovno telo

sa B4-rezni prsten

sa B3-rezni prsten

| Seriya | PN<br>[bar] | Prečnik cevi | M      | L1 | L2   | L3   | L4 | L5 | CH1 | CH2 | Tip<br>Osnovno telo | Tip<br>B4-prsten  | Tip<br>B3-prsten |
|--------|-------------|--------------|--------|----|------|------|----|----|-----|-----|---------------------|-------------------|------------------|
| L      | 160         | 22           | 26x1,5 | 35 | 27,5 | 43,5 | 15 | 44 | 27  | 36  | C-WE22LM26X1,571X   | C-WE22ZLM26X1,571 | C-WE22LM26X1,571 |
|        |             | 28           | 33x2   | 38 | 30,5 | 49   | 17 | 47 | 36  | 41  | C-WE28LM33X271X     | C-WE28ZLM33X271   | C-WE28LM33X271   |
|        |             | 35           | 42x2   | 45 | 34,5 | 57   | 19 | 56 | 41  | 50  | C-WE35LM42X271X     | C-WE35ZLM42X271   | C-WE35LM42X271   |
|        |             | 42           | 48x2   | 51 | 40   | 64   | 20 | 63 | 50  | 60  | C-WE42LM48X271X     | C-WE42ZLM48X271   | C-WE42LM48X271   |
| S      | 400         | 20           | 27x2   | 37 | 26,5 | 43,5 | 15 | 48 | 27  | 36  | C-WE20SM27X271X     | C-WE20ZSM27X271   | C-WE20SM27X271   |
|        |             | 25           | 33x2   | 42 | 30   | 49   | 17 | 54 | 36  | 46  | C-WE25SM33X271X     | C-WE25ZSM33X271   | C-WE25SM33X271   |
|        |             | 30           | 42x2   | 49 | 35,5 | 57   | 19 | 62 | 41  | 50  | C-WE30SM42X271X     | C-WE30ZSM42X271   | C-WE30SM42X271   |
|        |             | 315          | 48x2   | 57 | 41   | 64   | 20 | 72 | 50  | 60  | C-WE38SM48X271X     | C-WE38ZSM48X271   | C-WE38SM48X271   |

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - pocinkovani čelik ISO 8434-1 (DIN 2353) / koleno sa spoljnim navojem serije C-WE-M

Verzija 11

138487 / Generisano 2026/38 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

