


Sealing screw Series A-VSTI-R-ED-71



Design type	Sealing screw
Male thread	1/8...1 1/2" BSP, with elastic seal
Material	Stainless steel 1.4571
according to standard	EN ISO 8434-1 (DIN 2353)
Seal	FKM
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-25...+200°C
Operating pressure	Nominal pressure according to table up to 50°C, above 50°C 4,5% Pressure reduction, above 100°C 11% Pressure reduction

Dimensions



Series	PN [bar]	G	D1	L1	L2	CH1	Type
S	400	1/8	14	12,3	8	5	A-VSTIR1/8ED71
		1/4	19	17,3	12	6	A-VSTIR1/4ED71
		3/8	22	17,3	12	8	A-VSTIR3/8ED71
		1/2	27	19,3	14	10	A-VSTIR1/2ED71
		3/4	32	21,3	16	12	A-VSTIR3/4ED71
		1	40	22,8	16	17	A-VSTIR1ED71
	250	1 1/4	50	22,8	16	22	A-VSTIR1 1/4ED71
		1 1/2	55	22,8	16	24	A-VSTIR1 1/2ED71

Illustrations non-binding
Design, dimensional and material changes reserved

