


Flow monitor Series FM02-N



Design type	Flow monitor with reed switch contact, All-metal version, Float measuring principle, Air scale
Connection	G1/4" ... G1"
Materials	Body brass nickel-plated, Internal parts brass, Spring 1.4571, Hard ferrite magnet, Seals NBR
Application range	Air free of solid or magnetic particles, other gases on request
Medium temperature	-20...+120°C
Ambient temperature	-20...+120°C
Switching contact	Normally closed (NC) (Changeover contact as special version)
Switching point adjustment	Switching point adjustment by shifting the switching contact
Accuracy	+/- 10% from the full-scale value
max. operating pressure	250 or rather 300bar see table
Pressure drop	see table
max. voltage	see table
max. current	see table
Power	see table
Degree of protection	IP65 according to EN 60529 with correctly installed cable entry (protection against dust ingress and splashing water)
Mounting	Installation in rigid piping system
Mounting position	any
Scope of delivery	including device socket
Special version	Seals FKM or EPDM, Electrical contact for media temperatures up to 160°C, more contacts, Changeover contact, Switch in ATEX version, Switch with UL approval, IP67 with 1 m molded-on cable or rather Reed switch with M12 connection
Application note	Provide a straight pipe length of 10xDN upstream of the device and 5xDN downstream of the device. Never reduce the pipe diameter upstream of the device. The reed switches used in the switching contacts are, by design, very sensitive to overload. None of the values for voltage, current and power may be exceeded. Appropriate contact protection measures must be implemented depending on the electrical load.



Dimensions - Reed switch 15x50, connector according to EN175301-803 Form C



Connection G	Nominal size DN[mm]	A4	D1	D2	L1	T	SW	Weight [approx. g]
G1/4"	8	57	17	17	65	10	17	140


Connection	Switching range [Nl/min]*	Pressure drop [bar]	max. operating pressure [bar]	max. voltage [V]**	max. current [A]**	max. power [VA]**	Type
G1/4"	0,6...2,2	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-2,2
G1/4"	1,7...6	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-6
G1/4"	2,5...8	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-8
G1/4"	3...12	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-12
G1/4"	3...22	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-22
G1/4"	7...24	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-24
G1/4"	12...34	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-34
G1/4"	16...56	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-56
G1/4"	20...80	0,02...0,2	300	AC140 / DC200	AC0,7 / DC1	20	FM02-14-N-80

* Switching range for air at 1 bar absolute and 20°C. The specified switching values apply for decreasing flow and flow from bottom to top. For other inlet pressures and temperatures, different setting ranges apply.

** Switching capacity Changeover contact: AC/DC 150V, 1A, 3...20VA



Dimensions - Reed switch 15x50, connector according to EN175301-803 Form C




Connection G	Nominal size DN[mm]	A4	D1	D2	L1	L2	T	SW	Weight [approx. g]
G1/2"	15	67	-	31,2	90	-	14	27	350

Connection	Switching range [Nl/min]*	Pressure drop [bar]	max. operating pressure [bar]	max. voltage [V]**	max. current [A]**	max. power [VA]**	Type
G1/2"	2,5...10	0,02...0,3	300	230	3	60	FM02-12-N-10
G1/2"	5,5...20	0,02...0,3	300	230	3	60	FM02-12-N-20
G1/2"	8...30	0,02...0,3	300	230	3	60	FM02-12-N-30
G1/2"	10...35	0,02...0,3	300	230	3	60	FM02-12-N-35
G1/2"	45...90	0,02...0,3	300	230	3	60	FM02-12-N-90
G1/2"	55...220	0,02...0,3	300	230	3	60	FM02-12-N-220
G1/2"	65...240	0,02...0,3	300	230	3	60	FM02-12-N-240
G1/2"	80...300	0,02...0,3	300	230	3	60	FM02-12-N-300
G1/2"	140...525	0,02...0,3	300	230	3	60	FM02-12-N-525

* Switching range for air at 1 bar absolute and 20°C. The specified switching values apply for decreasing flow and flow from bottom to top. For other inlet pressures and temperatures, different setting ranges apply.
** Switching capacity Changeover contact: 250V, 1,5A, 3...50VA

Dimensions - Reed switch 30x70, connector according to EN175301-803 Form A




Connection G	Nominal size DN[mm]	A4	D1	D2	L1	L2	T	SW	Weight [approx. g]
G3/4"	20	99	40	47	130	152	15	34	1240
G1"	25	99	-	47	130	-	17	41	1030

Connection	Switching range [Nl/min]*	Pressure drop [bar]	max. operating pressure [bar]	max. voltage [V]**	max. current [A]**	max. power [VA]**	Type
G3/4"	60...180	0,02...0,4	250	250	3	100	FM02-34-N-180
G3/4"	100...300	0,02...0,4	250	250	3	100	FM02-34-N-300
G3/4"	200...650	0,02...0,4	250	250	3	100	FM02-34-N-650
G1"	60...180	0,02...0,4	250	250	3	100	FM02-10-N-180
G1"	100...300	0,02...0,4	250	250	3	100	FM02-10-N-300
G1"	200...650	0,02...0,4	250	250	3	100	FM02-10-N-650

* Switching range for air at 1 bar absolute and 20°C. The specified switching values apply for decreasing flow and flow from bottom to top. For other inlet pressures and temperatures, different setting ranges apply.

** Switching capacity Changeover contact: 250V, 1,5A, 3...50VA

Electrical connection



Illustrations non-binding
Design, dimensional and material changes reserved