


## Spojnice DN 7,2mm Serija C0.72-N




|                      |                                                                                            |
|----------------------|--------------------------------------------------------------------------------------------|
| Konstrukcija         | Utičnice spojnice i utikači spojnice, jednosmerno zatvaranje                               |
| Nazivni prečnik      | DN 7,2mm                                                                                   |
| Materijali           | Telo, ventil i konektor Niklovani mesing, Opruga od nerđajućeg čelika 1.4310, Zaptivka NBR |
| Nominalni protok     | 960Nl/min pri 6bar ( $\Delta p$ 0,5bar)                                                    |
| Medij                | Komprimovani vazduh, neutralni gasovi i tečnosti                                           |
| Temperatura medijuma | -20...+100°C                                                                               |
| Radni pritisak       | -0,87...35bar                                                                              |


### C0C72-M Utičnica spojnice - Spoljašnji navoj

|  | D1    | D2 | L1 | L2 | CH | Težina [g] | Tip         |
|-------------------------------------------------------------------------------------|-------|----|----|----|----|------------|-------------|
|                                                                                     | G1/8" | 27 | 7  | 38 | 22 | 70         | C0C72-M18-N |
|                                                                                     | G1/4" | 27 | 9  | 39 | 22 | 73         | C0C72-M14-N |
|                                                                                     | G3/8" | 27 | 9  | 41 | 22 | 76         | C0C72-M38-N |
|                                                                                     | G1/2" | 27 | 10 | 44 | 24 | 87         | C0C72-M12-N |

### C0C72-F Utičnica spojnice - Unutrašnji navoj


|  | D1    | D2 | L1   | L2 | CH | Težina [g] | Tip         |
|-------------------------------------------------------------------------------------|-------|----|------|----|----|------------|-------------|
|                                                                                     | G1/4" | 27 | 9    | 39 | 22 | 90         | C0C72-F18-N |
|                                                                                     | G1/4" | 27 | 10,5 | 41 | 22 | 92         | C0C72-F14-N |
|                                                                                     | G3/8" | 27 | 10,5 | 41 | 22 | 85         | C0C72-F38-N |
|                                                                                     | G1/2" | 27 | 12   | 43 | 24 | 87         | C0C72-F12-N |

### C0C72-H Utičnica spojnice - Nastavak za crevo


|  | Unutrašnji prečnik creva | D2 | L2 | Težina [g] | Tip         |
|-------------------------------------------------------------------------------------|--------------------------|----|----|------------|-------------|
|                                                                                     | 6                        | 27 | 55 | 64         | C0C72-H06-N |
|                                                                                     | 8                        | 27 | 55 | 67         | C0C72-H08-N |
|                                                                                     | 9                        | 27 | 55 | 68         | C0C72-H09-N |
|                                                                                     | 10                       | 27 | 55 | 70         | C0C72-H10-N |
|                                                                                     | 13                       | 27 | 55 | 75         | C0C72-H13-N |




### C0P72-M Priključni utikač - Spoljašnji navoj

|  | D1    | L1 | CH | Težina [g] | Tip         |
|-----------------------------------------------------------------------------------|-------|----|----|------------|-------------|
|                                                                                   | G1/8" | 31 | 13 | 17         | C0P72-M18-N |
|                                                                                   | G1/4" | 33 | 17 | 21         | C0P72-M14-N |
|                                                                                   | G3/8" | 33 | 19 | 26         | C0P72-M38-N |
|                                                                                   | G1/2" | 35 | 24 | 41         | C0P72-M12-N |
|                                                                                   |       |    |    |            |             |

### C0P72-F Priključni utikač - Unutrašnji navoj

|  | D1    | L1 | CH | Težina [g] | Tip         |
|-----------------------------------------------------------------------------------|-------|----|----|------------|-------------|
|                                                                                   | G1/8" | 30 | 13 | 19         | C0P72-F18-N |
|                                                                                   | G1/4" | 33 | 17 | 26         | C0P72-F14-N |
|                                                                                   | G3/8" | 33 | 19 | 26         | C0P72-F38-N |
|                                                                                   | G1/2" | 35 | 24 | 37         | C0P72-F12-N |
|                                                                                   |       |    |    |            |             |

### C0P72-S Priključni utikač - Priključak creva

|  | D1   | L1 | Težina [g] | Tip           |
|-----------------------------------------------------------------------------------|------|----|------------|---------------|
|                                                                                   | 6/4  | 34 | 18         | C0P72-S06-N   |
|                                                                                   | 8/6  | 34 | 19         | C0P72-S08-N   |
|                                                                                   | 10/8 | 43 | 38         | C0P72-S10-N-A |
|                                                                                   |      |    |            |               |

### C0P72-H Priključni utikač - Nastavak za crevo

|  | Unutrašnji prečnik creva | L1 | Težina [g] | Tip         |
|-------------------------------------------------------------------------------------|--------------------------|----|------------|-------------|
|                                                                                     | 6                        | 44 | 14         | C0P72-H06-N |
|                                                                                     | 8                        | 44 | 18         | C0P72-H08-N |
|                                                                                     | 9                        | 44 | 17         | C0P72-H09-N |
|                                                                                     | 10                       | 44 | 19         | C0P72-H10-N |
|                                                                                     | 13                       | 44 | 24         | C0P72-H13-N |

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica DN 7,2 - niklovani mesing

