

T-fitting Series C-T



Main body with nut and cutting ring




B4-Cutting ring




B3-Cutting ring

Design type	Compression fitting with cutting ring, with B3 or B4 cutting ring
Tube outside diameter	4...42mm
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	B3-Cutting ring -40...+120°C B4-Cutting ring NBR -35...+100°C (FKM on request)
Operating pressure	Nominal pressure according to table


Dimensions



Main body



with B4 cutting ring



with B3 cutting ring



Series	PN [bar]	Tube diameter	L1	L2	L3	CH1	CH2	Type Main body	Type with B4 ring	Type with B3 ring
LL	100	4	15	11	21	9	10	C-T04LLX	-	C-T04LL
		6	15	9,5	21	9	12	C-T06LLX	-	C-T06LL
		8	17	11,5	23	12	14	C-T08LLX	-	C-T08LL
L	315	6	19	12	27	12	14	C-T06LX	C-T06ZL	C-T06L
		8	21	14	29	12	17	C-T08LX	C-T08ZL	C-T08L
		10	22	15	30	14	19	C-T10LX	C-T10ZL	C-T10L
		12	24	17	32	17	22	C-T12LX	C-T12ZL	C-T12L
		15	28	21	36	19	27	C-T15LX	C-T15ZL	C-T15L
		18	31	23,5	40	24	32	C-T18LX	C-T18ZL	C-T18L
	160	22	35	27,5	44	27	36	C-T22LX	C-T22ZL	C-T22L
		28	38	30,5	47	36	41	C-T28LX	C-T28ZL	C-T28L
		35	45	34,5	56	41	50	C-T35LX	C-T35ZL	C-T35L
		42	51	40	63	50	60	C-T42LX	C-T42ZL	C-T42L
S	630	6	23	16	31	12	17	C-T06SX	C-T06ZS	C-T06S
		8	24	17	32	14	19	C-T08SX	C-T08ZS	C-T08S
		10	25	17,5	34	17	22	C-T10SX	C-T10ZS	C-T10S
		12	29	21,5	38	17	24	C-T12SX	C-T12ZS	C-T12S
		14	30	22	40	19	27	C-T14SX	C-T14ZS	C-T14S
	400	16	33	24,5	43	24	30	C-T16SX	C-T16ZS	C-T16S
		20	37	26,5	48	27	36	C-T20SX	C-T20ZS	C-T20S
		25	42	30	54	36	46	C-T25SX	C-T25ZS	C-T25S
		30	49	35,5	62	41	50	C-T30SX	C-T30ZS	C-T30S
		38	57	41	72	50	60	C-T38SX	C-T38ZS	C-T38S

Illustrations non-binding

Design, dimensional and material changes reserved

[Pneumatics](#) / [Fittings and couplings](#) / [Tube fittings](#) / [Tube fittings - Zinc plated steel ISO 8434-1 \(DIN 2353\)](#) / [T-fitting Series C-T](#)

