

## Adjustable T-fitting Series C-ET



Main body with nut and cutting ring



B4-Cutting ring




B3-Cutting ring

|                       |                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------|
| Design type           | Compression fitting with cutting ring, with sealing cone and O-ring and with B3 or B4 cutting ring |
| Tube outside diameter | 6...42mm                                                                                           |
| Material              | Steel galvanized                                                                                   |
| according to standard | EN ISO 8434-1 (DIN 2353)                                                                           |
| Medium                | neutral liquids and gases that do not attack the materials used                                    |
| Medium temperature    | B3-Cutting ring -35...+100°C<br>B4-Cutting ring NBR -35...+100°C (FKM on request)                  |
| Operating pressure    | Nominal pressure according to table                                                                |



## Dimensions



| Series | PN<br>[bar] | Tube diameter | m      | L1 | L2   | L3   | L4 | CH1 | CH2 | Type<br>Main body | Type<br>with B4 ring | Type<br>with B3 ring |
|--------|-------------|---------------|--------|----|------|------|----|-----|-----|-------------------|----------------------|----------------------|
| L      | 500         | 6             | 12x1,5 | 19 | 12   | 26   | 27 | 12  | 14  | C-ET06LX          | C-ET06ZL             | C-ET06L              |
|        |             | 8             | 14x1,5 | 21 | 14   | 27,5 | 29 | 12  | 17  | C-ET08LX          | C-ET08ZL             | C-ET08L              |
|        |             | 10            | 16x1,5 | 22 | 15   | 29   | 30 | 14  | 19  | C-ET10LX          | C-ET10ZL             | C-ET10L              |
|        | 400         | 12            | 18x1,5 | 24 | 17   | 29,5 | 32 | 17  | 22  | C-ET12LX          | C-ET12ZL             | C-ET12L              |
|        |             | 15            | 22x1,5 | 28 | 21   | 32,5 | 36 | 19  | 27  | C-ET15LX          | C-ET15ZL             | C-ET15L              |
|        |             | 18            | 26x1,5 | 31 | 23,5 | 35,5 | 40 | 24  | 32  | C-ET18LX          | C-ET18ZL             | C-ET18L              |
|        | 250         | 22            | 30x2   | 35 | 27,5 | 38,5 | 44 | 27  | 36  | C-ET22LX          | C-ET22ZL             | C-ET22L              |
|        |             | 28            | 36x2   | 38 | 30,5 | 41,5 | 47 | 36  | 41  | C-ET28LX          | C-ET28ZL             | C-ET28L              |
|        |             | 35            | 45x2   | 45 | 34,5 | 51,5 | 56 | 41  | 50  | C-ET35LX          | C-ET35ZL             | C-ET35L              |
|        |             | 42            | 52x2   | 51 | 40   | 56   | 63 | 50  | 60  | C-ET42LX          | C-ET42ZL             | C-ET42L              |
| S      | 800         | 6             | 14x1,5 | 23 | 16   | 27   | 31 | 12  | 17  | C-ET06SX          | C-ET06ZS             | C-ET06S              |
|        |             | 8             | 16x1,5 | 24 | 17   | 27,5 | 32 | 14  | 19  | C-ET08SX          | C-ET08ZS             | C-ET08S              |
|        |             | 10            | 18x1,5 | 25 | 17,5 | 30,5 | 34 | 17  | 22  | C-ET10SX          | C-ET10ZS             | C-ET10S              |
|        | 630         | 12            | 20x1,5 | 29 | 21,5 | 31,5 | 38 | 17  | 24  | C-ET12SX          | C-ET12ZS             | C-ET12S              |
|        |             | 14            | 22x1,5 | 30 | 22   | 35   | 40 | 19  | 27  | C-ET14SX          | C-ET14ZS             | C-ET14S              |
|        |             | 16            | 24x1,5 | 33 | 24,5 | 36,5 | 43 | 24  | 30  | C-ET16SX          | C-ET16ZS             | C-ET16S              |
|        | 420         | 20            | 30x2   | 37 | 26,5 | 44,5 | 48 | 27  | 36  | C-ET20SX          | C-ET20ZS             | C-ET20S              |
|        |             | 25            | 36x2   | 42 | 30   | 50   | 54 | 36  | 46  | C-ET25SX          | C-ET25ZS             | C-ET25S              |
|        |             | 30            | 42x2   | 49 | 35,5 | 55,5 | 62 | 41  | 50  | C-ET30SX          | C-ET06ZS             | C-ET30S              |
|        |             | 38            | 52x2   | 57 | 41   | 63   | 72 | 50  | 60  | C-ET38SX          | C-ET06ZS             | C-ET38S              |

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Adjustable T-fitting Series C-ET

Version 10

138456 / Generated 2026/40 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

