


Maintenance unit G3/4"...G1" Series Gold MU304




Design type	Diaphragm pressure regulator with secondary venting, Centrifugal force principle filter, Sintered filter element, Proportional lubricator, Oil filling under pressure possible
Connection	G3/4"...G1" according to ISO228/1
Materials	Housing Zinc die casting, Oil and condensate reservoir Polycarbonate or Metal
Function	Pressure regulation with filtration and enrichment of the compressed air with oil
Filter element	5µm
Mounting type	Installation in piping system or Wall mounting using mounting bracket
Mounting position	vertical, Drain screw bottom
Medium	Compressed air
Oil recommendation	HP32A (Temperature range 0...50°C), NR32 (Temperature range -35...85°C)
Oil metering	1...2 drops/min at $Q_N = 1000 \text{ NI/min}$
Medium temperature	with plastic bowl 0...+60°C, with metal bowl 0...+60°C (with appropriately conditioned compressed air - 10...+60°C)
Ambient temperature	with plastic bowl 0...+60°C, with metal bowl -10...+60°C
Inlet pressure	1,5...16bar or rather 1,5...20bar loud table, with automatic drain valve 1,5...16bar
Control ranges	0,5...10bar and 0,5...16bar with metal bowl (0,5...3/ 0,5...6 on request)
Flow direction	is marked by an arrow
Scope of delivery	including pressure gauge
Special version	Inlet pressure 25bar



Order code

MU304 - 34 - 0,5/10 - P - F5 - A1									
	3/4"	34							
Connection	1"	10							
Pressure range	0,5...10bar		0,5/10						
	0,5...16bar		0,5/16						
Reservoir	Plastic reservoir (Leave blank)								
	Plastic reservoir with protective cage					P			
	Metal container					M			
Filter element	5µm						F5		
Drain valve	semi-automatic drain valve (Leave blank)								
	automatic drain valve							A1	

Dimensional drawing



A1: automatic drain valve


Connection G	A	B	C	D	E	F	G1	H	I	J	K	L	M	N	O
G3/4"	308	196,5	26,5	158,5	50	6,2	G1/4"	M20x1,5	218	58	87	71,5	63	228	34
G1"	296	196,5	26,5	158,5	50	6,2	G1/4"	M20x1,5	218	58	87	71,5	63	228	34

Connection	Flow rate at 6 bar* [NI/min]	max. inlet pressure [bar]	Pressure range [bar]	Weight [approx. kg]	Type
G3/4"	5000	16	0,5...10	3,8	MU304-34-0,5/10-F5
G3/4"	5000	16	0,5...10	4,3	MU304-34-0,5/10-P-F5
G3/4"	5000	20	0,5...16	4,1	MU304-34-0,5/16-M-F5
G1"	5000	16	0,5...10	3,6	MU304-10-0,5/10-F5
G1"	5000	16	0,5...10	4,1	MU304-10-0,5/10-P-F5
G1"	5000	20	0,5...16	4	MU304-10-0,5/16-M-F5

*Flow rate data at inlet pressure of 8bar, outlet pressure of 6bar and 1bar Pressure drop



Flow diagram, Oiler response threshold



Accessories

Designation	Type
Holding angle with neck nut for pressure regulators M20x1,5	MMP04-38/10
Holding angle with 2 screws for lubricators and filters	MMB04-38H/10

Illustrations non-binding
Design, dimensional and material changes reserved