



Stainless steel flanged ball valves Series 720000




Design type	Shut-off valve with floating ball, full bore passage, Compensation hole
Actuation	by 90° rotation of the hand lever
Connection	Flanges DN15...DN150 according to EN1092-1, PN16
Materials	Body and ball stainless steel 1.4301, Ball seal PTFE, Spindle seal PTFE/FKM, Hand lever steel plastic-coated
Application range	Fluids and gases of Group 1 and 2 in accordance with PED 2014/68/EU that do not attack the materials used. For steam applications we recommend using special steam valves.
Medium temperature	-20...+160°C
Operating pressure	Vacuum max. 10 ⁻³ Torr up to Rated pressure according to table and pressure-temperature diagram
Mounting type	Installation in rigid piping system
Mounting position	any
Approvals	TA-Luft
Special versions	antistatic version ATEX EX II 2G Ex h IIC T6...T1 Gb / II 2D Ex h IIIC T85°C...T450°C Db, Fire-safe, Flange ANSI, Flange PN40, low dead-volume seals, Heating jacket for viscous media, Version for steam, oil-, grease- and silicone-free for oxygen, Low-temperature version





Nominal size DN[mm]	PN [bar]	A	B	C	D	E	F	L	ØN	R	P	T	Y	Z	Kv value [m³/h]	Weight [approx. kg]	Type
15	16	47	4xM5	15,5	90	10	7	35	32	131	65	9	65	4xM12	19,2	1,40	720000-15
20	16	51,5	4xM5	15,5	100	10	7	40	32	131	69	9	75	4xM12	35,0	1,90	720000-20
25	16	61	4xM5	17	115	12	8	46	42	174	80	11	85	4xM12	64,5	2,20	720000-25
32	16	64,5	4xM5	15	140	12	8	54	42	174	84	11	100	4xM16	103,8	3,30	720000-32
40	16	78	4xM6	24,5	150	16	10	63,5	50	250	102	13	110	4xM16	174	4,20	720000-40
50	16	87	4xM6	25	165	16	10	82	50	250	111	13	125	4xM16	301,3	6,10	720000-50
65	16	104,5	4xM8	25	185	20	14	103	70	321	128	18	145	4xM16	545,7	10,00	720000-65
80	16	115	4xM8	28,5	200	20	14	122	70	321	138	18	160	8xM16	872,5	13,50	720000-80
100	16	137	4xM10	34,5	220	24	18	152	102	381	156	22	180	8xM16	1363,3	20,90	720000-100
125	16	159	4xM10	34	250	24	18	196	102	381	178	22	210	8xM16	2360,3	40,50	720000-125
150	16	201,5	4xM12	51,5	285	42	30	232	125	700	266	30	240	8xM20	3671,1	64,10	720000-150

Pressure-temperature diagram



Illustrations non-binding
Design, dimensional and material changes reserved

Armatures / Ball valves - manually operated / Flanged ball valves - stainless steel / Flanged ball valve Series 720000

Version 10

150449 / Generated 2026/39 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

